

## Packaging Box for Face Milling Cutters and Shell End Mills

- sturdy, protective, humidity and oil resistant
- secure twist-type closure
- easy handling, re-usable
- tool is secured centrally in the pack by means of spigot locating in tool arbor hole
- adaptor rings to suit the various arbor hole sizes
- foam pad insert to be put into cover of pack for additional protection available

### Availability:

- **L** = in neutral from stock
- **S** = please enquire

### Material:

- Polyethylene (PE)

*Note: Technical modification and availability subject to change without notice.*



## rose plastic AG

Rupolzer Straße 53  
D-88138 Hergensweiler/Lindau  
Tel. ++49/83 88/92 00-0  
Fax ++49/83 88/10 24  
info@rose-plastic.de  
www.rose-plastic.de

| Ref        | L/S | Ø<br>mm | Length variable<br>from - to/mm | Box<br>Qty. |
|------------|-----|---------|---------------------------------|-------------|
| MK 80 050  | L   | 80      | 050 - 060                       | 170         |
| MK 80 070  | L   | 80      | 070 - 080                       | 120         |
| MK 80 090  | L   | 80      | 090 - 100                       | 100         |
| MK 80 110  | L   | 80      | 110 - 120                       | 80          |
| MK 80 130  | S   | 80      | 130 - 140                       | 80          |
| MK 100 060 | L   | 100     | 060 - 070                       | 95          |
| MK 100 070 | L   | 100     | 070 - 080                       | 70          |
| MK 100 090 | L   | 100     | 090 - 100                       | 65          |
| MK 100 110 | L   | 100     | 110 - 120                       | 60          |
| MK 100 130 | L   | 100     | 130 - 140                       | 50          |
| MK 100 150 | S   | 100     | 150 - 160                       | t.b.a.      |
| MK 100 170 | S   | 100     | 170 - 180                       | t.b.a.      |
| MK 100 200 | S   | 100     | 200 - 210                       | 32          |
| MK 125 065 | L   | 125     | 065 - 075                       | 56          |
| MK 125 075 | L   | 125     | 075 - 085                       | 50          |
| MK 125 090 | L   | 125     | 090 - 100                       | 40          |
| MK 125 110 | L   | 125     | 110 - 120                       | 35          |
| MK 125 130 | L   | 125     | 130 - 140                       | 30          |
| MK 125 150 | S   | 125     | 150 - 160                       | 25          |
| MK 125 170 | S   | 125     | 170 - 180                       | 24          |
| MK 125 200 | S   | 125     | 200 - 210                       | 20          |
| MK 180 065 | L   | 180     | 065 - 075                       | 30          |
| MK 180 075 | L   | 180     | 075 - 085                       | 24          |
| MK 180 090 | L   | 180     | 090 - 100                       | 24          |
| MK 180 110 | S   | 180     | 110 - 120                       | 18          |
| MK 180 130 | S   | 180     | 130 - 140                       | 15          |
| MK 180 150 | S   | 180     | 150 - 160                       | 12          |
| MK 180 170 | S   | 180     | 170 - 180                       | 10          |
| MK 180 200 | S   | 180     | 200 - 210                       | 12          |

### Securing Inserts for MK-Pack

|            | Ref.        | Arbor  | Depth | Box Qty. |
|------------|-------------|--------|-------|----------|
| for MK 80  | ST 80/22    | 22 mm  | 20 mm | 300      |
| for MK 100 | ST 100/22   | 22 mm  | 20 mm | 200      |
| for MK 125 | ST 125/22   | 22 mm  | 20 mm | 120      |
| for MK 180 | ST 180/40   | 40 mm  | 20 mm | 80       |
| for MK 180 | ST 180/38,1 | 1 1/2" | 20 mm | 80       |

### Adaptor Rings for MK-Pack

| metric     | Box Qty. | Inch                  | Box Qty. |
|------------|----------|-----------------------|----------|
| Ring 27/22 | 2000     | Ring 25,4/22 (1,00")  | 2000     |
| Ring 32/22 | 1500     | Ring 31,75/22 (1,25") | 1500     |
| Ring 40/22 | 1000     | Ring 38,1/22 (1,50")  | 1500     |
|            |          | Ring 50,8/40 (2,00")  | 1000     |

Note: When deciding on the depth for MK-Pack the thickness of any foam insert and securing insert should be taken into consideration.